# **HP Latex 700 Printer**



# Grow with high-value jobs and sharpen your sustainability edge with HP Latex Technology



### Win the high-value jobs you are after

- Deliver vivid colours at high speed and get striking contrast using pure blacks.
- Expect reliable, sharp 4-point text with HP Latex printheads featuring 10-picoliter ink drops.
- Choose from a wide application range covering banners/textiles/poster paper, canvas, wallpaper, and vinyl.

### Beat your deadlines with smart, efficient printing

- Fast saturated colour up to 31 m<sup>2</sup>/hr outdoor, 21 m²/hr indoor.
- Control print operations virtually anytime, anywhere with HP PrintOS tools, and grow with HP Learn trainings.
- Work fast processing reprints and multi-copy jobs with a smart front panel, and store up to 100 jobs.
- Enjoy fast and easy spindle-less loading and media access for rolls up to 55 kg.

### Sharpen your sustainability edge with HP Latex

- Innovative water-based HP Latex Inks—no HAPs<sup>2</sup>, no required hazard warning labels, and odorless prints.3
- Zero landfill—local outer carton recycling, free take-back of inner ink bag/printhead, HP Planet Partners.4
- Choose from a wide range of compatible ecoconscious media.5
- HP Latex prints are recyclable, returnable, or non-hazardous and safe for disposal.6

# For more information, please visit http://www.hp.com/go/latex700series

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://hplatexknowledgecenter.com/

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

<sup>1</sup> Outdoor mode (Banner) 4-pass, 100%. Indoor mode (SAV) 6-pass, 100%. Based on internal HP testing in September 2020 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.

<sup>2</sup> HP Latex Inks were tested for Hazardous Air Pollutants, as defined in the Clean Air Act, per U.S. Environmental Protection Agency Method 311 (testing conducted in 2013) and none were detected.

<sup>&</sup>lt;sup>3</sup> There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

<sup>4</sup> The ink cartridge HP Eco-Carton outer carton is 100% recyclable through local cardboard/paper programs. Inner materials including the ink bag are 55% recyclable and can be returned free of charge to the HP Planet Partners program for reprocessing of plastic parts. Zero landfill. For ink bag and printhead take back, visit http://www.hp.com/recycle to see how to participate and for HP Planet Partners program availability; program may not be available in your jurisdiction. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposal.

<sup>5</sup> See http://www.hp.com/go/mediasolutionslocator

<sup>6</sup> Most HP large format paper-based printing materials can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the free, convenient HP Large Format Media take-back programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details. HP large format printing materials, both unprinted and printed with Original HP Latex Inks, are non-hazardous and safe for disposal. Contact your local waste management authority for local area-specific instructions.

### **Technical specifications**

#### Print

Printing modes	105 m²/hr - Max Speed (1-pass) 31 m²/hr - High Speed (4-pass) 21 m²/hr - Production Fast (6-pass) 17 m²/hr - Production Fast (6-pass) 17 m²/hr - Production Quality, Textiles and Backlits (8-pass) 16 m²/hr - High Saturation (12-pass) 12 m²/hr - High Saturation Backlist and Textiles (14-pass)		
Print resolution	Up to 1200 x 1200 dpi		
Ink types	Water-based HP Latex Inks		
Ink cartridges	8 (black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer, HP Latex Overcoat)		
Cartridge size	1L		
Printheads	8 (2 cyan/black, 2 magenta/yellow, 2 light cyan/light magenta, 1 HP Latex Optimizer, 1 HP Latex Overcoat)		
Long-term print-to-print repeatability	95% of colours ≤ 1.5 dE2000 <sup>2</sup>		
Media			
Handling	Roll feed, take-up reel, wiper roller <sup>3</sup> , automatic horizontal cutter (for vinyl, banner and canvas <sup>4</sup> , paper-based media, and film)		
Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall coverings, canvas, synthetics, mesh, textiles <sup>5</sup>		
Roll size	457 to 1625-mm rolls (580 to 1625-mm rolls with full support)		
Roll weight	55 kg		
Roll diameter	250 mm		
Thickness	Up to 0.5 mm		
Applications	Banners; Displays; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Window graphics; Stickers		
Connectivity			
Interfaces	Gigabit Ethernet (1000Base-T)		
Dimensions (w x d	x h)		
Printer	2583 x 852 x 1402 mm		
Shipping	2800 x 1130 x 1270 mm		
Operating area	2793 x 2100 mm		
Operating area  Weight	2793 x 2100 mm		
Weight	2793 x 2100 mm 261 kg		
<b>Weight</b> Printer			
<b>Weight</b> Printer	261 kg		
Weight Printer Shipping What's in the box	261 kg 362 kg  HP Latex 700 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor		
Weight Printer Shipping What's in the box Environmental ran	261 kg 362 kg  HP Latex 700 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor		
Weight Printer Shipping What's in the box Environmental ran Operating temperature	261 kg  362 kg  HP Latex 700 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor  ges		
Weight Printer Shipping What's in the box Environmental ran Operating temperature Operating humidity	261 kg  362 kg  HP Latex 700 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C		
Weight Printer Shipping What's in the box Environmental ran Operating temperature Operating humidity Acoustics	261 kg  362 kg  HP Latex 700 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C		
Weight Printer Shipping What's in the box Environmental ran Operating temperature Operating humidity Acoustics Sound pressure	261 kg  362 kg  HP Latex 700 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)		
Weight Printer Shipping What's in the box Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power	261 kg  362 kg  HP Latex 700 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)  60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)		
Weight Printer Shipping What's in the box Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power	261 kg  362 kg  HP Latex 700 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)  60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)		
Weight Printer Shipping What's in the box Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption	261 kg  362 kg  HP Latex 700 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)  60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)		
Weight Printer Shipping What's in the box Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption	261 kg  362 kg  HP Latex 700 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)  60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)  1.5-2.5 kW (5 kW peak) (printing), 95 W (ready)  Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 9 A max		
Weight Printer Shipping What's in the box Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements	261 kg  362 kg  HP Latex 700 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)  60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)  1.5-2.5 kW (5 kW peak) (printing), 95 W (ready)  Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 9 A max		
Weight Printer Shipping What's in the box Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements Certification Safety	261 kg  362 kg  HP Latex 700 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)  60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)  1.5-2.5 kW (5 kW peak) (printing), 95 W (ready)  Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 9 A max printer power cord; 13 A max curing power cord		
Weight Printer Shipping What's in the box Environmental ran Operating temperature Operating humidity Acoustics Sound pressure Sound power Power Consumption Requirements Certification	261 kg  362 kg  HP Latex 700 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor  ges  15 to 30°C  20 to 80% RH (non-condensing)  60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)  7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)  1.5-2.5 kW (5 kW peak) (printing), 95 W (ready)  Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 9 A max printer power cord; 13 A max curing power cord  IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC)  Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and		

### Ordering information

HP Latex 700 Printer

### Product YOU 22A

Accessories		
21V10A	HP Latex 700/800 User Maintenance Kit	
421S3A	HP Latex Media Feed Accessory	
7HR16A	HP Latex 700/800 Textile Kit Accessory	
7HR18A	HP Latex 700/800 Ink Collector Foams Kit	
7HR19A	HP Latex 700/800 Media Loading Accessory	
T7U73A	HP Latex 500/700/800 Wiper Roller	

### Original HP printing supplies

4UU94A	HP 836 Optimizer Latex Printhead	
4UU96A	HP 836 Latex Maintenance Cartridge	
4UV75A	HP 832 1-liter Black Latex Ink Cartridge	
4UV76A	HP 832 1-liter Cyan Latex Ink Cartridge	
4UV77A	HP 832 1-liter Magenta Latex Ink Cartridge	
4UV78A	HP 832 1-liter Yellow Latex Ink Cartridge	
4UV79A	HP 832 1-liter Light Cyan Latex Ink Cartridge	
4UV80A	HP 832 1-liter Light Magenta Latex Ink Cartridge	
4UV81A	HP 832 1-liter Optimizer Latex Ink Cartridge	
4UV82A	HP 832 1-liter Overcoat Latex Ink Cartridge	
4UV95A	HP 836 Black/Cyan Latex Printhead	
4UV96A	HP 836 Magenta/Yellow Latex Printhead	
4UV97A	HP 836 Light Cyan/Light Magenta Latex Printhead	
4UV98A	HP 836 Overcoat Latex Printhead	

### Original HP large format printing materials

- HP PVC-free Wallpaper (UL GREENGUARD GOLD Certified<sup>6</sup>, FSC<sup>®</sup> certified<sup>7</sup>, meets AgBB criteria<sup>8</sup>) HP Photo-realistic Poster Paper HP Premium Satin Canvas HP Prime Matte Air GP (REACH compliant<sup>9</sup>) HP Premium Removable Gloss Adhesive Vinyl (REACH compliant<sup>9</sup>)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com

### Service and Support

U13D9E HP 2 year Next Business Day with Defective Media Retention
U13DFE HP 3 year Next Business Day with Defective Media Retention
U13DKPE HP 1 year Post Warranty Next Business Day with Defective Media Retention
U13DQPE HP 2 year Post Warranty Next Business Day with Defective Media Retention

## ECO highlights

- Inks do not use reactive monomer chemistry, are ozone-free, and meet the ZDHC standard <sup>1</sup> Can win new business with odourless prints, UL ECOLOGO®/UL GREENGUARD Gold Certified ink, and more <sup>2</sup> Eco-Carton replaces plastic cartridge with 80% reduction in Jastic, achieves 66% CO2e reduction <sup>3</sup> Zero landfill—local outer carton recycling, free take-back inner ink bag via HP Planet Partners <sup>4</sup>

# Please recycle printing hardware and eligible printing supplies and prints. Find out how at our website: http://www.hp.com/ecosolutions

<sup>1</sup> See http://www.roadmaptozero.com . Printing with HP Latex Inks avoids the problematic reactive monomers associated with UV printing. Acrylate monomers present in uncured UV inks and UV-gel inks can damage skin.

<sup>2</sup> There is a broad set of media with very different odour profiles. Some of the media can affect the odour performance of the final print. For certifications, see http://www.ul.com/lg. and http://www.ul.com/lg.

<sup>3</sup> CQ2e reduction based on moving from plastic ink cartridge to cardboard HP Eco-Carton ink cartridge, with annual manufacturing savings of 29 I tons and transport savings of 8 I tons. Equivalent to 1,194,028 km (741,935 miles) driven by an average passenger vehicle or over 38 million smartphones charged.

<sup>4</sup> The ink cartridge HP Eco-Carton outer carton is 100% recyclable through local cardboard/paper programs. Inner materials including the ink bag are 55% recyclable and can be returned free of charge to the HP Planet Partners program for reprocessing of plastic parts. Zero landfill. For take-back of ink bag/printhead/prints, visit http://www.hp.com/recycle to see how to participate and for HP Planet Partners program availability, program may not be available in your jurisdiction.

1 Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects.
2 The colour variation between printed jobs has been measured at 12 pass mode on vinyl media. Reflective measurements on a 943 colour target under CIE standard Illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard D5 O14-6/E22012. Sw of colours may experience variations above 1.5 dE2000. Backlit substrates measured in transmission mode may yield different results.
3 Wiper roller is an optional accessory.
4 Automatic horizontal cutter is for use with thinner banners and anavas only. It is recommended to perform a test. 5 Textlie Kit Accessory required for long runs of textile and porous textile.
5 UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to ULS GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.ul.com/gg or http://www.ucom/gg or http://www.ucom/gg or http://www.greenguard.org
7 Trademark license code FSC-C115319,
8 With HP Latex links, prints meet AgBB criteria for health-related evaluation of VOC emissions. See http://urnweltbundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building

<sup>8</sup> With HP Latex links, prints meet Agilist criteria for neature-treated evaluation of Scholar Printp.//unmeiblundesamt.de/eln/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building
<sup>9</sup> This product does not contain substances listed as SVHC (15S) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.



























