

## Resin Coated Photo Premium Matte 260gsm

### FibaPrint® Range IFA-178

#### Product Description

Resin Coated (RC) high white flat matte photo paper, single side coating. Compatible with dye and pigment based aqueous inkjet printers.

#### Features

- RC inkjet photo paper
- High white
- Ultra Smooth flat matte surface
- Single side coated
- Exceptional colour gamut and D-max

#### Applications

- Fine art and photographic open and limited edition prints
- Original digital art and photo prints
- Art and photo portfolios, photo and wedding albums
- Posters and large format exhibition displays
- Glass free framing

Basic Weight (gsm)	260		
Paper Thickness (Microns)	275	Paper Thickness (Inches)	0.010
Base Material	Resin Coated		
Coating Type	Matte		
Surface Texture	Ultra Smooth		
Tint (L*a*b*)	L* = 95.47 a*=1.70 b*=-11.89 M1 (D50)		
Whiteness (CIE)	137		
Brightness (TAPPI)	103		
Opacity	96		
OBA Content	Yes		
pH	7.5-9.5		
Recyclable	Yes (PE recycle only)		
Print Settings*	MK Ink, Premium Matte, Matte Photo or Archival Matte Paper Settings are recommended as a starting point		
Notes			

\*Generic ICC Profiles for selected printer models are available from the Innova Art website.

Sheets	A4, A3, A3+, A2, 8.5x11", 13x19"
Rolls (30m Length)	60", 44", 36", 24", 17"

Additional sizes are available on request, subject to order quantity.

#### Handling and Storage

- All digital Fine Art Papers and Canvases are fragile and need to be handled with extreme care. Try not to touch the surface of the paper, always hold the paper by the edges and wear cotton gloves if necessary.
- Return unused material to the original box and only store finished prints in archival quality packaging. If mounting or framing, use only archive grade tapes and glues.
- After printing, leave prints open to the air to fully dry (24 hours is recommended). Do not stack prints on top of each other straight away.
- Using a giclée varnish or spray will help protect your print from damage, effects of UV light and environmental attack.

#### Conditions of Use

- The recommended climate for storage of all papers is 15-20°C, relative humidity of 40-60%. Always store in original packaging, out of direct sunlight and protected from moisture.
- Do not exceed temperatures of 82°C (180°F) when dry mounting.

All recommendations are for your guidance only. These are subject to our test criteria, which remain subject to change without prior notice.